

Standard SureGuide Tube and Shaft Sizes - Australia

Item Code	Belt Width "D" in mm	Bracket to Bracket "A" Stringer Length mm	Back to Back "B" Gauge Length mm	Roller Face "C" Length mm	Belt Width "D" In mm	Maximum Load in KG's
30 Series (30mm diameter shaft) (Roller - 168mm)						
SG45/30	450	700	560	500	610	550
SG60/30	600	850	710	650	760	500
SG75/30	750	1000	860	800	910	420
SG90/30	900	1150	1010	950	1060	350
SG100/30	1000	1250	1110	1050	1160	270
SG105/30	1050	1300	1160	1100	1210	250
SG120/30	1200	1450	1310	1250	1360	200
SG135/30	1350	1600	1460	1400	1510	150
40 Series (40mm diameter shaft) (Roller - 209mm)						
SG90/40	900	1150	1000	950	1060	750
SG105/40	1050	1300	1150	1100	1210	720
SG120/40	1200	1450	1300	1250	1360	580
SG135/40	1350	1600	1450	1400	1510	382
SG140/40	1400	1650	1500	1450	1560	370
SG150/40	1500	1750	1600	1550	1660	365
SG160/40	1600	1850	1700	1650	1760	310
SG165/40	1650	1900	1750	1700	1810	260
SG180/40	1800	2050	1900	1850	1960	220
50 Series (50mm diameter shaft) (Roller - 235mm)						
SG105/50	1050	1300	1150	1100	1210	820
SG120/50	1200	1450	1300	1250	1360	780
SG135/50	1350	1600	1450	1400	1510	750
SG140/50	1400	1650	1500	1450	1560	670
SG150/50	1500	1750	1600	1550	1660	620
SG165/50	1650	1900	1750	1700	1810	600
SG180/50	1800	2050	1900	1850	1960	500
SG200/50	2000	2250	2100	2050	2160	450
SG210/50	2100	2350	2200	2150	2260	400
SG220/50	2200	2450	2300	2250	2360	350
SG240/50	2400	2650	2500	2450	2560	300

